# **SkillsUSA University**

### **60 AUTODESK INVENTOR TIPS IN 60 MINUTES**

#### J.D. Mather – Pennsylvania College of Technology

For educators and students in mechanical design.

A rapid paced delivery of the top tips and tricks gathered from years of experience teaching Autodesk Inventor software. Looking for that one class that will justify your travel to SkillsUSA University - if you teach mechanical design/drafting using Autodesk Inventor - this is it. After this class, when you return to your home school you will be referred to as the Inventor Guru. 1 p.m., Big Joe Turner A.

#### **Key Learning**

Basic Interface Settings BORN Technique Robust Sketch Techniques Neutral File Translation Basic Assembly Tips Drawing Tips

#### About the Speaker:

J.D. Mather is an Assistant Professor of CAD and Product Design at Pennsylvania College of Technology, Penn State. He previously worked in industry for 15 years, including positions as journeyman machinist, research and development technician, and industrial engineering technician. Dr. Mather has been an Autodesk Inventor Certified Expert since release 7. He is also a Certified SolidWorks Professional. He is experienced with AutoCAD and Pro/E as well. Dr. Mather placed second for Autodesk Inventor category at the Autodesk University 2006, Avatech Altogether Smarter Challenge, and placed first in the same category at AU 2007. He has presented AutoCAD and Inventor classes at Autodesk University 2006-2009.

Reference Materials: http://home.pct.edu/~jmather/SkillsUSA University.pdf http://home.pct.edu/~jmather/content/DSG322/inventor surface tutorials.htm http://www.autodesk.com/discussiongroup-inventor http://www.vdssolutions.co.uk/



**Tip 1.** You should be aware that you and your students can get a free learning license of many Autodesk products including Inventor Professional from the Autodesk Student Community.



General	Save	File	Colors	Display	Hardware	Prompts	Drawing	
Notebook	Ske	tch	Part	iFeature	Assembly	Conte	ent Center	
2D Sketch								
Constra	int placeme	nt priority	y	Displa	ау			
Para	allel and per	pendicula	r	G	rid lines			
Hori	zontal and v	vertical		M	inor grid lines	3		
Overcor	nstrained di	mensions		A:	xes			
				C	oordinate system	n indicator		
	iy unven uir	nension		Di	splay coincident eation	constraints o	n	
War	n of overco	nstraineo	d condition		Constra	int and DOF		
					symbol s	scale		
Spline fi	t method				s-Up Display			
Stan	dard			🗸 Er	☑ Enable Heads-Up Display (HUD)			
Auto	CAD				Settings			
Minin	um Eperav	- Default	Tension	U	Securigan			
	num Energy	Derau	C TENSION					
Ų								
0			100					
Snap t	o grid		$\frown$					
V Edit di	- mension wh	en create	ed 4					
Autop	roject edge	s durina a	urve creation					
	roject edge	s for sket	ch creation ar	nd edit 5				
	t sketch pla	ne on ske	etch creation		)			
Autop	roject part (	prigin on a	sketch create	$\left( \begin{array}{c} \\ \end{array} \right)$				
Report alignment				$\mathbf{U}$				
2D Skotch	ingrimerit							
Auto-h	end with 3	) line crea	ation					
and the second sec								

Tip 3. On the sketch tab turn off Display – Grid items.

Tip 4. Turn on Edit dimension when created.

**Tip 5.** Turn off Autoproject edges for sketch creation and edit (Note: I will leave on for now to demonstrate later why you should turn it off).

Tip 6. Make sure Autoproject part origin on sketch create is always turned on.

General	Save	File	Colors	Display	Hardware	Prompts	Drawing
Notebook	Sket	ch	Part	iFeature	Assembly	Conte	nt Center
Sketch on	new part cre w sketch	eation		Constru Opa	uction aque surfaces		
Sketch	n on x-y plane	e					
Sketch	n on y-z plane	e					
Sketd	n on x-z plane	e					

**Tip 7.** On the Part tab you might want to set No new sketch – when you start a new part you will select the plane on which to create the first sketch rather than Inventor automatically starting the first sketch.



plication Optio	ons		00	V		×
General S	ave File	Colors	Display	Hardware	Prompts	Drawing
Notebook	Sketch	Part	iFeature	Assembly	Conte	nt Center
🔲 Defer updat	e					
Delete comp	onent pattern s	source(s)				
Enable cons	traint redundan	cy analysis				
📃 Enable relati	ed constraint fa	ilure analysis				
E Features are	e initially adapti	ve				
Section all p	arts					
Use last occ	urrence orienta	tion for compon	ent placement			
🔽 Constraint a	udio notification	)	_			
Display comp	oonent names a	fter constraint i	names			

**Tip 9** I would uncheck Constraint audio notification and checkmark Display component names after constraint names on the Assembly tab. (Set opposite of the default settings I show here.)



One of the most powerful features of Inventor is the use of geometric constraints like tangent, collinear, horizontal, vertical and perpendicular.

We use these geometry constraints so frequently that it makes sense to assign "hotkeys" on the keyboard to quickly access these constraints.

If you use the Inventor sketcher properly most of your geometry constraints will be applied automatically, but there will still be a frequent need to manually place constraints.

I have not seen any evidence that working without constraints is faster than working with constraints. I <mark>could be wrong, but I doubt it.</mark> Select the Keyboard tab and then the Categories – Sketch. Click to the left of the command for which you want to define a hotkey.

Custor	mize	_	910.1					×
Tool	bars Comman	ds Keyboa	rd					
		Cate	nories Sketch		•	Y	All	•
					-	<b>C</b>		
Ke	eys	Cor	2D Intersection Cur	240	Type	Cate	gory -b	
		¥	Auto Dimension	ve		Sketa	th	=
		<u> </u>	Bend			Sketo	:h	
			Center Arc			Sketo	:h	
			Center Point		Alian	Sketo	:h	
	A C	Ó	Center Point Arc		Alias	Sketo	n h	
	-	¥.	Centerline		14140	clust		
		C C	Chamfer	Tip 10 The period	d key (on	the		
			Circular Pattern	Numerical keypa	d) remino	ds me	e of the	
	lum.		Coincident	Inventor coincide	ent consti	raint	glyph.	
		0	Concentric					
		×	Connection Point G	rip		Sketo	:h	-
•								•
	Lice default mu	lti charactor	Command Aliacoa					
	USE DETAULT ITU	iu-character	Command Allases					
							Po	est All Kove
							Ke	SELAILKEYS
Des	scription –							
	Makes	points or cur	ves coincident				Сору	to Clipboard
a					<b></b>			
				Import	Export.	••	Reset A	ll Close
N	lum -	<b>V X</b> <del>~~</del>	Horizontal	Tin 11 Then mi	nus kov i	s a hr	vrizontal	line
		22		IIP II Men III	nus key i	5 a m	5112011tai	inte.
N	lum +	<b>√×</b> √	Perpendicular	Tip 12 The plus	kev is tw	vo pe	rpendicu	llar lines.
				···• ···• • ···•	,	- 1		
N	lum *	<b>VXò</b>	Tangent	Tip 13 The aste	risk remi	nds r	ne of a c	ircle.
								-
N	lum /		Vertical	Tip 14 The forw	vard slasł	n key	is almos	t vertical.
				•		,		

All of these settings can be Exported for Import on another machine.

olor $\bullet$ $f_x = \bullet$ Autodesk In View Environments Get Started Add-Ins Sketch	ventor Professional 2011 - STUDENT VER Tip 15   see a lo reports of peop
Shadows •     Image: Orthographic •     Image: Skee Gr       Reflections •     Image: Ground Plane •     Color       Two Lights •     •	Interface Screen Switz
Appearance 🕶	ViewCube Fine You can get it ba ViewCube Fine Fine Fine Fine Fine Fine Fine Fin
	Status BarNotice that any tab is your activ environment.

of е ser

ck ıb –

green



Tip 16 In this class we are going to use the Base Orphan Reference Node Technique (Born Technique).

In this class use the origin geometry to your advantage. It has no parents and cannot be deleted. It will always be there for you. Use it to anchor your work. Use it for symmetry. Use it for consistency. You don't have to have it visible to use it.

## Just Use it!



**Tip 17** Sketch one line, or a circle, a rectangle or a polygon and dimension it **immediately**.

This will give you a sense of scale for the rest of your sketch. In general – keep your sketches simple – I recommend no more than 7-10 entities in most sketches.

**Tip 18** Following the BORN Technique create your sketches as much as practical on origin workplanes rather than on part faces.

![](_page_7_Figure_4.jpeg)

**Tip 19** Watch out for the Constraint Persistence icon (particularly before Inventor 2011) as it looks very much like the Perpendicular constraint.

Beginners hit this and don't realize they have turned off auto-constraints.

![](_page_8_Figure_0.jpeg)

Tip 20 Using a horizontal and vertical line to midpoints can lead to unexpected results.

![](_page_8_Figure_2.jpeg)

Tip 21 Using a horizontal and vertical constraints to midpoints can lead to unexpected results.

![](_page_9_Picture_0.jpeg)

**Tip 22** The most robust technique I have found is to use a diagonal construction line to constrain rectangles with symmetry about the origin.

Notice that a sketch changes color when it is fully constrained/dimensioned.

Make generous use of construction lines.

**Tip 23** You can click the right mouse button and turn on sketch Degrees of Freedom as a visual guide to what dimensions/constraints are

needed in a sketch.

I recommend simply dragging endpoints.

![](_page_9_Figure_7.jpeg)

![](_page_9_Figure_8.jpeg)

Inventor will automatically place many constraints.

**Tip 24** You can go directly into a arc while in the line command by clicking and dragging off the endpoint of the line.

**Tip 25** If you click on a circle and hold the mouse button down and drag your second endpoint to a second circle Inventor will automatically place tangent constraints at both endpoints.

![](_page_10_Figure_1.jpeg)

![](_page_10_Figure_2.jpeg)

**Tip 26** Avoid the use of Mirror of sketch entities if possible.

Use Symmetry constraints instead.

![](_page_10_Figure_5.jpeg)

![](_page_11_Figure_0.jpeg)

Tip 28 You can use window selection or crossing window selection just like AutoCAD.

![](_page_11_Figure_2.jpeg)

**Tip 31** You can enter units at any time and mix and match appropriate units as well as use function operators. If the equation in the dialog box is red then it is not valid – if black then it is valid.

![](_page_11_Figure_4.jpeg)

**Tip 32** Offsetting an ellipse results in different solutions depending on where you select the ellipse. One result is a mathematic ellipse, the other is a constant offset distance.

![](_page_12_Picture_0.jpeg)

**Tip 33** Remember earlier I suggested turning off the default Autoproject edges on sketch create. Notice how complex this sketch is with autoproject turned on.

![](_page_12_Figure_2.jpeg)

**Tip 34** Copy sketches and features to save time and effort. Toggle endpoints to centerpoints for hole placement. You can Ctrl unselect hole centerpoint locations.

![](_page_13_Picture_0.jpeg)

**Tip 35** You can click and drag off of a planar face while in the Workplane command or simply start a new sketch and click and drag off of the planar face. (It is useful to know every method of creating a workplane.)

**Tip 36** When placing text sketch, dimension the text box immediately – it doesn't matter what the dimensions are.

![](_page_13_Picture_3.jpeg)

**Tip 37** A workplane has a front side and a backside. Right Mouse button click on the workplane and select Flip Normal to flip a user created workplane.

Tip 38 A dimensioned text box can be dragged to any angle (predictable results from lower left corner).

![](_page_14_Picture_0.jpeg)

**Tip 39** The Rectangular feature pattern command should probably be called Curve Driven Pattern.

But sometimes you can get unexpected results. In this case the design intent was for the patterned slots to cut entirely through the solid just like the first slot.

![](_page_14_Figure_3.jpeg)

**Tip 40** The design intent can be achieved by expanding the dialog box and selecting Adjust under the Compute heading.

![](_page_15_Figure_0.jpeg)

**Tip 41** For a more complex curve driven pattern expand the dialog box and move the Start Point to an appropriate location and set Orientation to Direction 1.

The design intent is for a pattern of tapped holes going around the cylinder and up the face of the cylinder.

Looks like a Circular pattern and a Rectangular pattern will be needed.

**Tip 42** But the design intent can be accomplished with one "Rectangular Pattern.

![](_page_15_Picture_5.jpeg)

![](_page_16_Picture_0.jpeg)

**Tip 43** The first part brought in to an assembly is automatically grounded at the origin, but I recommend also constraining the first component to the origin by adding 3 Mate-Flush constraints between the XY, XZ and YZ planes.

**Tip 44** You can use Place Component or simply drag and drop from Explorer to Assembly.

Tip 45 In an assembly set your browser to Modeling View to gain access to part feature tree.

![](_page_16_Figure_4.jpeg)

**Tip 46** Feature Patterns can be used to generate Component Patterns.

![](_page_17_Picture_0.jpeg)

**Tip 47** You can use the edge of surfaces for a curve driven pattern.

**Tip 48** I usually don't worry too much about Top, Front or Right Side – it is all relative. You can change how your part is viewed on opening a file.

![](_page_17_Picture_3.jpeg)

**Tip 49** To add this icon to the Navigation Bar click on the arrow in the circle. You can then easily change view styles without going to the View ribbon tab.

PRO	Model	Inspect	Tools	Man	age	View	Environn	nents	
🥖	<b>V</b>			7					
Stress Analysis	Inventor Studio	AEC Exchange	Conver Sheet N	rt to /letal	Add-In	s			
	Begin		Conv	ert	Manag	e			
Environments Get Started Add-Ins AEC Exchange									
Ĺ,		•		Ê			$\checkmark$	Тір	
UCS	Save As DWG Soli	s Check D ds	esign E	(port B Compo	Building onents	AEC	inish Exchange	goir Excl	
			Exit	Soli					

**Tip 50** You can Export DWG Solids by going to the Environments tab>AEC Exchange and select Save As DWG Solids.

**Tip 51** When reusing AutoCAD data in Inventor you can opt to Open in idw environment or Import into ipt environment.

File Open Option	s
Non-Inventor D	WG File
🔘 Open	
Import	
0	OK Cancel

**Tip 52** There are many other proprietary and neutral format file types that can be imported as well. Sometimes imported data is not of the highest quality. For information on repairing neutral format dat in Inventor see <a href="http://au.autodesk.com/?nd=class&session\_id=3056">http://au.autodesk.com/?nd=class&session\_id=3056</a>.

You might also review the other AU On-line Classes available on Inventor.

![](_page_19_Picture_0.jpeg)

**Tip 53** You can use scanned hand-drawn sketches or photographs as reference for creating models. Just don't take the imported image too literally (especially if, like me, you aren't an artist – add your design flare in Inventor).

![](_page_19_Picture_2.jpeg)

You might want to test out the kinematics<sup>1</sup> of a mechanism before taking time to fully model the components.

1. The branch of mechanics that deals with pure motion, without reference to the masses or forces involved in the motion.

Create schematic block representation of your mechanism.

![](_page_20_Figure_1.jpeg)

At this point we can test the 2D motion but not the 3D motion of the crank handle. Eventually we will want to create 3D components for each part of the mechanism, so let's go ahead and push out the individual parts now and create an assembly.

![](_page_20_Figure_3.jpeg)

You must be in Sketch mode – click on the Make Components icon.

Make Components : Selection		$\mathbf{X}$
Remove from selection     Base   LL Arm   LI Arm   LI Arm   LI Arm   LI Arm   Lift Plate   Crank Handle	<ul> <li>✓ Insert components in target assem</li> <li>Target assembly name</li> <li>Scissors Jack.iam</li> <li>Target assembly location</li> <li>C:\Documents and Settings\jmather</li> <li>Default BOM structure</li> <li>▲ Normal</li> </ul>	nbly Template Standard.iam
		Next>> Cancel

Select all of the blocks from the browser to create components.

Μ	ak	e (	Components: Blocks					×		
						]				
			Selected Blocks	Component Name	*	Template	BOM Structure	File Location		
	۲		Base	Base.ipt	Ø	Standard.ipt	<b>₽</b> ∎Normal	[Source Path]		
		-	LL Arm	LL Arm.ipt	٦	Standard.ipt	<b>₽</b> ∎Normal	[Source Path]		
			LR Arm	LR Arm.ipt	O	Standard.ipt	<b>₽</b> ∎Normal	[Source Path]		
	UL Arm UL Arm.ipt 🗇				٦	Standard.ipt	<b>₽</b> ∎Normal	[Source Path]		
		UR Arm UR Arm.ipt		D	Standard.ipt	<b>₽</b> ∎Normal	[Source Path]			
			Jack Screw	Jack Screw.ipt	O	Standard.ipt	<b>₽</b> ∎Normal	[Source Path]		
			Lift Plate	Lift Plate.ipt	D	Standard.ipt	<b>₽</b> ∎Normal	[Source Path]		
		l	Crank Handle	dle 🛛 Crank Handle.ipt 🗂 Standard.ipt 📲 Normal		<b>₽</b> ∎Normal	[Source Path]			
	Component position options									
l	✓ Constrain to layout plane									
(	OK Cancel Apply									

Make sure the Component position options are selected for constraining.

![](_page_22_Figure_0.jpeg)

We now have an assembly of components.

If we try to drag a component to test the motion we see that we have an unconstrained parallelogram. In the real world assembly the gear teeth on the arms will keep them parallel, but as we haven't modeled the parts yet we will have to add an extra assembly constraint.

Application Options			×
General       Save       File       Colors       Display       Ha         Notebook       Sketch       Part       iFeature         Defer update       Defer update       Delete component pattern source(s)         Enable constraint redundancy analysis       Enable related constraint failure analysis         Features are initially adaptive       Section all parts         Use last occurrence orientation for component placement         Constraint audio notification         Display component names after constraint names	ardware	Prompts	Drawing
	Assembly	Conter	nt Center

Before we continue it will be helpful to go to Tools>Application Options>Assembly tab and turn on Display component names after constraint names.

![](_page_23_Figure_0.jpeg)

To force the Lift Plate to remain horizontal as the mechanism moves we place an angle zero mate assembly constraint between the XZ Plane of the assembly and the XZ Plane of the Lift Plate.

![](_page_23_Figure_2.jpeg)

Since we haven't modeled the teeth on the arms yet we need to un-suppress the YZ Flush constraint that Inventor automatically applied to the Lift Plate.

Now we need to go through the rest of the assembly constraints that were automatically placed by Inventor and set the appropriate condition for each. A strong understanding of assembly constraints is required to complete the rest of the problem. A disciplined step-by-step approach is required or it is easy to become confused. I expand each part one-by-one and analyze each constraint and the effect on the assembly. The Base component is fully constrained – so we don't need to change any of its constraints.

![](_page_24_Figure_1.jpeg)

The Lower Left Arm (LL Arm) motion is constrained to the XY Plane – it needs to be free to move up and down on the XY Plane. It is constrained at one end to the Base and on the other end to the UL arm. No changes need to be made. The constraints on all of the arms are correct.

![](_page_24_Figure_3.jpeg)

The Jack Screw need to be free to rotate, therefore we need to Suppress the XY Flush constraint.

**Tip 54** Be careful – as you change between 2D and 3D Kinematics the constraint number and position in the list changes. You must change all three remaining constraints on the Jack Screw to 3D Kinematic. Check the Crank Handle – suppress the XY Flush constraint and verify that the Mate between the Crank Handle and the Jack Screw is set to 3D Kinematic. The actual identification numbers of the

![](_page_25_Picture_1.jpeg)

constraints were created automatically by Inventor and might be different for you. Pay attention to the part names.

Place Constrain	t 🔀	
Assembly Motion	Transitional Constraint Set	
Distance: 1.000 in		
ОК	Cancel Apply	

Testing our mechanism we see that the 2D motion is correct – we need to add one final constraint to get the 3D Motion. For now We will leave the Distance (ratio) on 1 as we can change that at any time. The easiest way to check the 2D and 3D kinematic motion is to click and drag the Lift Plate.

![](_page_25_Figure_5.jpeg)

If you have Inventor Professional with Dynamic Simulation you can go beyond simple kinematics analysis and to a full Dynamic Simulation of the mechanism when you have the parts modeled. In this example the experiment was to see how the required input force would change

depending on hand placement on the Crank Handle and position of the Lift Plate.

![](_page_26_Figure_0.jpeg)

When creating 2D drawing views from 3D models the software creates the views quite literally – including details that might make the view a bit obscure. We can edit the view for clarity.

![](_page_26_Figure_2.jpeg)

**Tip 55** The job of editing can be simplified by judicious use of layers. I temporarily turn off the Visible line layer and select the lines I wish to hide. You can hide lines by right clicking and selecting Hide after selecting the entities to hide. Then turn the Visible line layer back on.

![](_page_26_Figure_4.jpeg)

**Tip 56** One of the most common questions that come up is, "How do I dimension to an apparent intersection?" It is actually quite easy, but takes a bit of practice at first. Pick the first line and then Right Mouse Button and select Intersection and click the intersecting line. In this example there are two projected intersections – so pick the third line and Right Mouse Button select the intersecting line again after opting for intersection.

![](_page_27_Picture_0.jpeg)

**Tip 57** When you are annotating a drawing you can gain Windows Character Map in any command that uses text.

![](_page_27_Picture_2.jpeg)

**Tip 58** What is the purpose of creating drawings?

To communicate design intent.

We can do what is needed to convey design intent while also incorporating standards. An example is the traditional practice of showing ribs in section.

ſ	About Autodesk Inventor I	Professional					
l	Autodo		🔙 Product Lic	ense Information			
	Invento	sk r°	License name: AutoCAD Inve	entor Professional Suite 2011	Computer host nam JDMather	e:	
l			Serial number:			Product key:	
		Professional	License type:		opuate	License expiration d	ate:
L			Standalone - L	.ocked		Saturday, June 11	, 2011
L			License behavi	or:	License usage type		
L			License ID:				
L			INVPRO_F_S				
	Autodesk® Inventor® Prof 32-Bit Edition - 2.00 GB	essional 2011	License Agree	ment	ctivate	Save	As
	Build: 239, Release: 2011 R	TM - Date: Wed 02/17/2	2010	© 2010 Autodesk, Inc. All rig	hts reserved.		
l	Usage Type: Educational Version			All use of this Software is sub of the Autodesk End User Lice	ject to the terms a ense Agreement ag	and conditions	
l	License Expiration:	6/11/2011		installation of this Software a	nd/or packaged wi	th the	
	Serial Number:	353-78330147		Sortware.			
	License Behavior:	Extendable				Ŧ	
				Product Info	ormation	ОК	

**Tip 59** If your students are running the student version on their own computers they can verify the license expiration date by going to Help>About Inventor>Product Information.

![](_page_28_Picture_2.jpeg)

**Tip 60 Do Not** double click on Big I - as this closes Inventor (or any Windows Ribbon program). Sometimes you might click on this icon and it is a bit slow to expand, you might then click again and the program suddenly closes. When students do this they might get the impression that the program just crashed, but this is normal Windows Ribbon behavior.

Thanks, and enjoy SkillsUSA University.

Send questions to jmather@pct.edu